
Operator AFFE_MODELE

1 Goal

To define the modelled physical phenomenon (mechanical, thermal or acoustic) and the type of finite elements.

This operator allows to affect modelings on whole or part of the grid, which defines:

- degrees of freedom on the nodes (and the equation or the associated conservation equations),
- types of finite elements on the meshes,

The possibilities of the finite elements being able to be selected are described in the booklets [U3].

The types of meshes are described in the document "Description of the file of grid of *Code_Aster*" [U3.01.00].

This operator also allows to define a distribution of the finite elements in order to parallel elementary calculations and the assemblies.

Product a structure of data of the type `model`.

2 Syntax

```

Mo [model] = AFFE_MODELE      (
    ♦ GRID = my,                / [grid]
                                / [skeleton]
    ♦ | AFFE                    = _F (
      ♦ / ALL                   = 'YES',
        / G ROUP_MA             = g_mail,                [l_gr_maille ]
      ♦ /♦ PHENOMENON           = 'MECHANICAL',
        ♦ MODELING              = (see [§3.2.1])
    If MODELING = '3D_HHO' or 'MODELISAION = 'D_PLAN_HHO'
      ♦ FORMULATION             = / 'LINEAR'             [DEFECT]
                                / 'QUADRATIC'           [TXT]
    FinSi
      /♦ PHENOMENON             = 'THERMAL'
      ♦ MODELING                = (to see [§3.2.1])
      /♦ PHENOMENE              = 'ACOUSTIC',
      ♦ MODELING                = (see [§3.2.1])
    | AFFE_SOUS_STRUC          = _F (
      ♦ / ALL                   = 'YES',
        / SUPER_MAILLE          = l_mail,                [l_maille]
    )
    ♦ VERI_JACOBIEN             = / 'YES'                [DEFECT]
                                / 'NOT'
    ♦ GRANDEUR_CARA             = _F (
      ♦ LENGTH                  = will lcar,             [R]
      ♦ PRESSURE                = will pcar,             [R]
      ♦ TEMPERATURE             = will tcar,             [R]
    ♦ DISTRIBUTION              = _F (
      ♦ METHOD =
                                / 'SOUS_DOMAINE'         [DEFECT]
      ♦ NB_SOUS_DOMAINE =/ nb_proc [DEFECT]
                                / nb_sous_dom
      ♦ PARTITIONNEUR =/ 'MONGREL'
    [DEFECT]
                                / 'SCOTCH TAPE'
                                / 'MAIL_CONTIGU'
      ♦ CHARGE_PROC0_MA =/100   [DEFECT]
                                / pct
                                / 'MAIL_DISPERS'
      ♦ CHARGE_PROC0_MA =/100   [DEFECT]
                                / pct
                                / 'GROUP_ELEM'
                                / 'CENTRALIZES'
      )
    ♦ INFORMATION = / 1
    [DEFECT]
                                / 2,
    )

```

3 Operands

3.1 Operand GRID

◆ GRID = my

Name of the grid associated under investigation on which one affects the elements.

Note: For axisymmetric modelings, the axis of revolution is the axis Y grid. All the structure must be with a grid in $X \geq 0$.

3.2 Keyword AFFE

◆ | AFFE

Defines the entities of the grid and the types of elements which will be affected for them. For each occurrence, one give a modeling.

The entities of the grid are specified by the operands:

Operands	Contents/significance
ALL	Assignment with the totality of the meshes
GROUP_MA	Assignment with a list of groups of meshes

The type of element is specified by the operands:

Operands	Contents/significance
PHENOMENON	Modelled physical phenomenon (associated conservation equation)
MODELING	Type of interpolation and discretization
FORMULATION	Type of formulation in certain cases

3.2.1 Operands PHENOMENON, MODELING and FORMULATION

◆ PHENOMENON
◆ MODELING
◇ FORMULATION

The first two keywords PHENOMENON and MODELING soNT obligatory for each occurrence of the keyword factor AFFE. This couple of keywords defines in a bijective way the type of affected element in a kind of mesh.

In certain cases, it can be necessary to specify FORMULATION employee:

- For the discretization of the type HHO (3D_HHO or D_PLAN_HHO), one can specify if it is a linear approach (FORMULATION=' LINEAIRE ') or quadratic (FORMULATION=' QUADRATIQUE ')

Note: the keyword PHENOMENON must have the same value for all the occurrences of the keyword factor AFFE .

Possible modelings are indicated below by listing them by “packages”:

ACOUSTICS

ACOUSTICS 2D continuous mediums
PLAN U3.33.01 and R4.02.01

ACOUSTICS 3D continuous mediums
3D U3.33.01 and R4.02.01

THERMICS

THERMICS 2D hull

COQUE_AXIS	U3.22.01 and R3.11.01
COQUE_PLAN	U3.22.01 and R3.11.01
THERMICS 2D continuous mediums	
AXIS_DIAG	U3.23.01 and R3.06.07
AXIS_FOURIER	U3.23.02
AXIS	U3.23.01 and R3.06.02
PLAN_DIAG	U3.23.01 and R3.06.07
PLAN	U3.23.01 and R3.06.02
THERMICS 3D hull	
HULL	U3.22.01 and R3.11.01
THERMICS 3D continuous mediums	
3D_DIAG	U3.24.01 and R3.06.07
3D	U3.24.01 and R3.06.02
MECHANICS 2D	
MECHANICS 2D discrete elements	
2D_DIS_TR	
2D_DIS_T	
MECHANICS 2D vibroacoustic fluid-structure	
2D_FLUIDE	U3.13.03 and R4.02.02
2D_FLUI_ABSO	U3.13.13 and R4.02.05
2D_FLUI_PESA	U3.14.02 and R4.02.04
2D_FLUI_STRU	U3.13.03 and R4.02.02
AXIS_FLUIDE	U3.13.03 and R4.02.02
AXIS_FLUI_STRU	U3.13.03 and R4.02.02
D_PLAN_ABSO	U3.13.12 and R4.02.05
MECHANICS 2D continuous mediums	
AXIS	U3.13.01 and R3.01.01
AXIS_FOURIER	U3.13.02
AXIS_SI	U3.13.05 and R3.06.10
C_PLAN_SI	U3.13.05 and R3.06.10
C_PLAN	U3.13.01 and R3.01.01
D_PLAN_SI	U3.13.05 and R3.06.10
D_PLAN	U3.13.01 and R3.01.01
MECHANICS 2D quasi incompressible	
AXIS_INCO_UP	R3.06.08
D_PLAN_INCO_UP	R3.06.08
AXIS_INCO_UPG	U3.13.07 and R3.06.08
D_PLAN_INCO_UPG	U3.13.07 and R3.06.08
MECHANICS 2D HHO	
D_PLAN_HHO	R3.06.14
MECHANICS 2D not room	
D_PLAN_GRAD_VARI	
D_PLAN_GVNO	R5.04.04
AXIS_GVNO	R5.04.04
D_PLAN_GRAD_SIGM	R5.03.24
MECHANICS 2D plates and hulls	
COQUE_AXIS	U3.12.02 and R3.07.02

MECHANICS 2D elements joined for the propagation of crack

PLAN_JOINT	U3.13.14 and R3.06.09
AXIS_JOINT	U3.13.14 and R3.06.09
PLAN_JOINT_HYME	R3.06.09 and R3.06.09
PLAN_INTERFACE	R3.06.13
PLAN_INTERFACE_S	R3.06.13
AXIS_INTERFACE	R3.06.13
AXIS_INTERFACE_S	R3.06.13

MECHANICS 2D elements with internal discontinuities for the starting and the propagation of crack

PLAN_ELDI	U3.13.14 and R7.02.14
AXIS_ELDI	U3.13.14 and R7.02.14

MECHANICS 2D thermo-hydro-mechanics

AXIS_HH2MD	R7.01.10
AXIS_HH2MS	R7.01.10
AXIS_HHMD	R7.01.10
AXIS_HHMS	R7.01.10
AXIS_HHM	U3.13.08 and R7.01.10
AXIS_HMD	U3.13.08
AXIS_HMS	R7.01.10
AXIS_HM	R7.01.10
AXIS_THH2D	R7.01.10
AXIS_THH2S	R7.01.10
AXIS_THH2MD	R7.01.10
AXIS_THH2MS	R7.01.10
AXIS_THHD	R7.01.10
AXIS_THHS	R7.01.10
AXIS_THHMD	R7.01.10
AXIS_THHMS	R7.01.10
AXIS_THMD	R7.01.10
AXIS_THMS	R7.01.10
AXIS_THM	U3.13.08 and R7.01.10
AXIS_HHD	R5.04.03
AXIS_HHS	R5.04.03
AXIS_HH2D	R5.04.03
AXIS_HH2S	R5.04.03

D_PLAN_HH2MD	R7.01.10
D_PLAN_HH2MS	R7.01.10
D_PLAN_HHMD	R7.01.10
D_PLAN_HHMS	R7.01.10
D_PLAN_HHM	U3.13.08 and R7.01.10
D_PLAN_HMD	R7.01.10
D_PLAN_HMS	R7.01.10
D_PLAN_HM	U3.13.08 and R7.01.10
D_PLAN_HM_P	U3.13.08
D_PLAN_THH2D	R7.01.10
D_PLAN_THH2S	R7.01.10
D_PLAN_THH2MD	R7.01.10
D_PLAN_THH2MS	R7.01.10
D_PLAN_THHD	R7.01.10
D_PLAN_THHS	R7.01.10
D_PLAN_THHMD	R7.01.10
D_PLAN_THHMS	R7.01.10
D_PLAN_THMD	R7.01.10
D_PLAN_THMS	R7.01.10
D_PLAN_THM	U3.13.08 and R7.01.10
D_PLAN_HHD	R5.04.03

D_PLAN_HHS	R5.04.03
D_PLAN_HS	R5.04.03
D_PLAN_HH2D	R5.04.03
D_PLAN_HH2S	R5.04.03
D_PLAN_2DG	R5.04.03
D_PLAN_DIL	R5.04.03

MECHANICS 2D hydraulics unsaturated with finished volumes

D_PLAN_HH2SUDA	R7.01.34
----------------	----------

MECHANICS 2D elements joined with hydraulic coupling

AXIS_JHMS	
PLAN_JHMS	

For the grids 2D, allows to inform the groups of meshes or the meshes likely to be crossed by the crack when the contact is defined on the lips of the crack. Are allowed the following types of meshes: QUAD8 and TRIA6 and the meshes of edge of these elements, are them SEG3. If the meshes are linear, they should as a preliminary be transformed into quadratic meshes (with LINE_QUAD of the operator CREA_MAILLAGE).

MECHANICS 3D

MECHANICS 3D bars and cables

2D_BARRE	R3.08.01
BAR	U3.11.01 and R3.08.01
CABLE_POULIE	U3.11.03 and R3.08.02
CABLE	U3.11.03 and R3.08.02
CABLE_GAINE	R3.08.10

MECHANICS 3D discrete elements

DIS_TR	U3.11.02
DIS_T	U3.11.02

MECHANICS 3D fluid-structure

3D_FAISCEAU	
3D_FLUIDE	U3.14.02 and R4.02.02

MECHANICS 3D absorbing border

3D_ABSO	U3.14.09 and R4.02.05
3D_FLUI_ABSO	U3.14.10 and R4.02.05

MECHANICS 3D grids of concrete reinforcements

GRILLE_MEMBRANE	U3.12.04 and R3.08.07
GRILLE_EXCENTRE	U3.12.04 and R3.08.07

MECHANICS 3D continuous mediums

3D_SI	U3.14.01 and R3.06.10
3D	U3.14.01 and R3.01.01

MECHANICS 3D not room

3D_GRAD_VARI	
3D_GVNO	R5.04.04

MECHANICS 3D plates, hulls and membranes

COQUE_3D	U3.12.03 and R3.07.04
DKT	U3.12.01 and R3.07.03
DST	U3.12.01 and R3.07.03
Q4G	U3.12.01 and R3.07.03
DKTG	U3.12.01 and R3.07.03
Q4GG	U3.12.01 and R3.07.09

MEMBRANE	U3.12.04 and R3.08.07
MECHANICS 3D beams	
FLUI_STRU	U3.14.02
LOUSE_FLUI_STRU	U3.14.02
POU_D_E	U3.11.01 and R3.08.01
POU_D_EM	U3.11.07 and R3.08.08
POU_D_SQUE	U3.11.07 and R3.08.08
POU_D_T	U3.11.01 and R3.08.01
POU_D_TGM	U3.11.04
POU_D_TG	U3.11.04
POU_D_T_GD	U3.11.05
MECHANICS 3D quasi incompressible	
3D_INCO_UP	R3.06.08
3D_INCO_UPG	U3.14.06 and R3.06.08
3D_INCO_UPO	R3.06.08
MECHANICS 3D HHO	
3D_HHO	R3.06.14
MECHANICS 3D thermo-hydro-mechanics	
3D_HHMD	
3D_HHM	U3.14.07 and R7.01.10
3D_HMD	
3D_HM	U3.14.07 and R7.01.10
3D_THHD	
3D_THHMD	
3D_THHM	U3.14.07 and R7.01.10
3D_THMD	
3D_THM	U3.14.07 and R7.01.10
3D_THVD	
3D_THH2MD	
3D_THH2M	
3D_HH2MD	
3D_HH2MS	
3D_THH2S	
3D_THH2D	
3D_HHD	R5.04.03
3D_HHS	R5.04.03
3D_HS	R5.04.03
3D_HH2D	R5.04.03
3D_HH2S	R5.04.03
MECHANICS 3D hydraulics unsaturated with finished volumes	
3D_HH2SUDA	R7.01.34
MECHANICS 3D pipes	
TUYAU_3M	U3.11.06 and R3.08.06
TUYAU_6M	U3.11.06 and R3.08.06

For the grids 3D, allows to inform the groups of meshes or the meshes likely to be crossed by the crack when the contact is defined on the lips of the crack. Are allowed the following types of meshes: HEXA20, PENTA15, TETRA10, and the meshes of edges of these elements, are them QUAD8 and TRIA6. If the meshes are linear, they should as a preliminary be transformed into quadratic meshes (with LINE_QUAD of the operator CREA_MALLAGE).

MECHANICS 3D elements joined for the propagation of crack

Warning : The translation process used on this website is a "Machine Translation". It may be imprecise and inaccurate in whole or in part and is provided as a convenience.

Copyright 2020 EDF R&D - Licensed under the terms of the GNU FDL (<http://www.gnu.org/copyleft/fdl.html>)

Titre : *Opérateur AFFE_MODELE*
Responsable : *ABBAS Mickaël*

Date : *02/06/2020* Page : *8/12*
Clé : *U4.41.01* Révision :
65e0c4d8d498

3D_JOINT	U3.13.14 and R3.06.09
3D_JOINT_HYME	R3.06.09 and R3.06.09
3D_INTERFACE	R3.06.13
3D_INTERFACE_S	R3.06.13

3.3 Keyword AFFE_SOUS_STRUC

◆ | AFFE_SOUS_STRUC

Is usable only for one using model of the static substructures [U1.01.04].

◆ / SUPER_MAILLE = l_mail

`l_mail` is the list of the super-meshes which one wants to affect in the model. As for the finite elements, it is not obligatory to affect all the meshes of the grid. It is `AFFE_MODELE` who confirms which are the substructures which will be used in the model. The difference with the classical finite elements is that on the super-meshes, one does not choose nor `MODELING` nor it `PHENOMENON` because the macronutrient (built by the operator `MACR_ELEM_STAT` [U4.62.01]) who will be affected on the super-mesh has his own modeling and his own phenomenon (those which were used to calculate it).

Caution! Your model must contain at least a finite element (keyword `AFFE` with the §3.2) when you use definite static substructures starting from a physical grid (read by `LIRE_MAILLAGE`) because it is not possible to have only macronutrients in this case.

/ ALL = 'YES'

All them (super) meshes are affected.

3.4 Operand VERI_JACOBIEN

◇ VERI_JACOBIEN = 'YES' / 'NOT'

This keyword is used to check that the meshes of the model are not distorted too much. One calculates the jacobien of the geometrical transformation which transforms the element of reference into each real mesh of the model. So on the various points of integration of a mesh, the jacobien changes sign, it is that this mesh is very "badly rotten". An alarm is then emitted.

3.5 Operand GRANDEUR_CARA

◇ GRANDEUR_CARA = _F (LENGTH = will lcar, ...)

This keyword is used to define some physical sizes characteristic of with the dealt problem. These sizes are currently used "have-to dimension" certain terms of the estimators of error in "HM". See [R4.10.05].

3.6 Keyword DISTRIBUTION

◇ DISTRIBUTION = _F (METHOD = methoof, ...)

This keyword makes it possible to distribute the finite elements of the model for the parallelism of elementary calculations, the assemblies and certain linear solveurs. Cf. [U2.08.06] "Note of use of parallelism".

It defines how (or not) the meshes/elements for the phases paralleled will be distributed of *Code_Aster*. The user thus has the possibility of controlling this distribution between the processors.

Parallelism operates:

- on elementary calculations and the assemblies of matrices and vectors (it is what the keyword factor `DISTRIBUTION` allows to control),
- with the resolution of the linear system if the solvor is paralleled (cf. [U4.50.01]).

In the case of new fashion of parallelism (grid parallel of type `maillage_p`), the mode of distribution is obligatorily `CENTRALIZE` because the grid has already was distributed and it is not possible of to redistribute calculations again. If another mode of distribution is selected for this mode of parallelism, it will be automatically rocked in mode `CENTRALIZE` without informing the user of it.

Notice : It is possible to modify the mode of distribution during its study. It is enough to use the order `MODI_MODELE [U4.41.02]`.

Note: It can be practical to continue a parallel calculation with a number of processors different from that used for initial calculation. In particular, one can want to carry out certain postprocessings into sequential. It is recommended to use the order `MODI_MODELE` to define the distribution to be used in continuation. More precisely, Lorsque initial calculation used it parallelism "by groups of elements" ('GROUP_ELEM' or 'SOUS_DOMAINE'), the order `MODI_MODELE` is useless. On the other hand, Lorsque initial calculation has used it parallelism "by elements" ('MAIL_CONTIGU' or 'MAIL_DISPERSÉ'), the order `MODI_MODELE` is obligatory. If it is forgotten, one is stopped during calculation by one error message.

3.7 Keyword METHOD

3.7.1.1 METHOD =/ 'CENTRALIZES'

Parallelism starts only on the level of the linear solver. Each processor builds and provides to the solver the entirety of the system to be solved. Elementary calculations are not paralleled. It is the method of distribution obligatory in the case of a parallel grid of type `maillage_p`.

3.7.1.2 METHOD =/ 'GROUP_ELEM'

CE mode of distribution allows a perfect balancing of load (in term of numbers of calculations elementary) *a priori*, i.e. each processor will carry out, for a kind of element given, the same number of elementary calculations (with near). Obviously that does not prejudice of anything the final balancing of load in particular in non-linear calculations where the cost of an elementary calculation depends on other parameters but the type of element.

In this mode, the elements of the model are gathered by "group" in order to pool certain calculations what makes it possible to gain in effectiveness. The number of elements by group can be selected in the order `BEGINNING [U4.11.01]`.

In addition, it is a question of the only mode able of distributing elementary calculations induced by the late elements, i.e. by the loadings such as the boundary conditions dualized or the continuous contact.

3.7.1.3 METHOD =/ 'MAIL_DISPERSÉ'

The distribution takes place on the meshes. They are distributed equitably on the various processors available. The meshes are distributed on the various processors as it is made it when one distributes cards to several players. One also speaks about "cyclic" distribution.

For example, with a model comprising 8 meshes, carried out on 4 processors, one obtains the following distribution:

Mode of distribution	Mesh 1	Mesh 2	Mesh 3	Mesh 4	Mesh 5	Mesh 6	Mesh 7	Mesh 8
MAIL_DISPERSÉ	Proc. 0	Proc. 1	Proc. 2	Proc. 3	Proc. 0	Proc. 1	Proc. 2	Proc. 3

It is seen that with this mode of distribution, a processor will treat meshes regularly spaced in the order of the meshes of the grid. The advantage of this distribution is that "statistically", each processor will treat as many hexahedrons, of pentahedrons, ..., and of triangles.

The workload for elementary calculations in general will be well distributed. On the other hand, the matrix assembled on a processor "will be very dispersed", contrary to what occurs for the mode 'MAIL_CONTIGU'.

3.7.1.4 METHOD =/ 'MAIL_CONTIGU'

The distribution takes place on the meshes. They are divided into packages of contiguous meshes on various processors available.

For example, with a model comprising 8 meshes, a machine of 4 processors available, the following distribution is obtained:

Mode of distribution	Mesh 1	Mesh 2	Mesh 3	Mesh 4	Mesh 5	Mesh 6	Mesh 7	Mesh 8
MAIL_CONTIGU	Proc. 0	Proc. 0	Proc. 1	Proc. 1	Proc. 2	Proc. 2	Proc. 3	Proc. 3

For this mode of distribution, the workload for elementary calculations can be less balanced. For example, a processor can have to treat only "easy" meshes of edge. On the other hand, the matrix assembled on a processor is in general more compact.

3.7.1.5 Keyword `CHARGE_PROC0_MA`

```
◇ CHARGE_PROC0_MA = /100 [DEFECT]
                    / pct
```

This keyword is accessible only for the modes from distribution 'MAIL_DISPERSÉ' and 'MAIL_CONTIGU'. Indeed these modes of distribution do not distribute in general equitably the load of calculations because of boundary conditions dualized whose elementary calculations are treated by processor 0.

If one wishes to relieve processor 0 (or on the contrary to overload it), one can use the keyword `CHARGE_PROC0_MA`. This keyword makes it possible to the user to choose the percentage of load which one wishes to assign to processor 0.

For example, if the user chooses `CHARGE_PROC0_MA = 80`, processor 0 will treat 20% of elements of less than the other processors, is 80% of the load which it should support if the division were equitable between the processors.

3.7.1.6 `METHOD = 'SOUS_DOMAINE'` [DEFECT]

This distribution of the meshes is based on a decomposition grid under-fields, built by a tool external of partitioning defined by the keyword `PARTITIONNEUR`:

```
◇ PARTITIONNEUR = / 'MONGREL' [ DEFECT ]
                  / 'SCOTCH TAPE'
```

The number of under-fields can be given by the user, via the keyword `NB_SOUS_DOMAINE`:

```
◇ NB_SOUS_DOMAINE = / nbproc [ DEFECT ]
                    / nb_sous_dom
```

By default, the number of under-fields is taken equal to the number of processors implied in calculation (`nbproc`).

The elements of the model finite elements carried by the meshes of each under-field are then distribute by groups of similar elements (as in the distribution corresponding to the method `GROUP_ELEM`), in order to balance elementary calculations as well as possible.

The preliminary partitioning of the grid under-fields makes it possible to ensure that all the elements of a group of finite elements belong to only one under-field.

4 Production run

Starting from the keywords PHENOMENON, MODELING and FORMULATION one creates a structure of data specifying the type of element attached to each mesh.

A brief recall of the assignments is systematically printed (INFO=1) in the file message.

5 Example

For a modeling of the phenomenon 'MECHANICAL', one affects on the group of meshes gma elements 3D isoparametric.

```
Mo = AFFE_MODELE ( GRID = my,  
                  AFFE = ( _F ( GROUP_MA = gma,  
                               PHENOMENON = 'MECHANICAL',  
                               MODELING = '3D' ),  
                  ) )
```